



TOPCon N type Mono-crystalline 410-430 Watt Full Black

0~+5W POWER TOLERANCE

High efficiency TOPCon N - type solar module



Module characteristics



Strong Mechanical Strength
Passes the wind load test of 2400Mpa and the snow load test of 5400Mpa



Lower attenuation
N-type, good reliability and lower LID/LETID attenuation rate



PID resistance
The attenuation probability of PID phenomenon is minimized through solar cell production technology optimization and raw material control



Harsh environmental adaptation
Robust design for demanding climate conditions.




Multiple busbar and Half cell technique
More light utilization and current collection capabilities, effectively improving product power output and reliability



Long and reliable quality assurance

IEC61215(2016), IEC61730(2016)
ISO9001:2015: Quality management system
ISO14001:2015: Environmental management system
ISO45001:2018: Occupational health and safety management system




Electrical Parameters


Model Type	ESM-410T		ESM-415T		ESM-420T		ESM-425T		ESM-430T	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	410	309.6	415	315	420	318	425	322	430	326
Open Circuit Voltage (Voc)	37.5	35.2	37.7	36.0	37.9	36.2	38.1	36.4	38.3	36.6
Short Circuit Current (Isc)	13.88	11.16	13.96	11.22	14.04	11.27	14.11	11.33	14.18	11.38
Maximum Power Voltage (Vmp)	31.6	29.2	31.8	29.8	32.0	30.0	32.2	30.2	32.4	30.3
Maximum Power Current (Imp)	12.98	10.62	13.06	10.56	13.13	10.62	13.20	10.67	13.28	10.74
Module Efficiency - η_m (%)	21.0		21.3		21.5		21.8		22.0	
Operational Temperature	-40°C ~ +85°C									
Maximum System Voltage	1500VDC									
Maximum Series Fuse Rating	25A									
Power Tolerance	0 ~ +3%									
Temperature Coefficient of Pmax	-0.310%/°C									
Temperature Coefficient of Voc	-0.260%/°C									
Temperature Coefficient of Isc	+0.046%/°C									
Nominal Operating Cell Temperature	45 ± 2°C									
Safety Class	Class II									
Max Load (Front/back)	5400Mpa/2400Mpa									

STC: Irradiance 1000W/m² Cell temperature 25°C Atmospheric quality = 1.5
 NOCT: Irradiance 800W/m² Ambient temperature 25°C Atmospheric quality = 1.5 Wind speed 1m/S

Mechanical Diagrams



Curve



Packing Details:

36pcs/pallet, Each pallet size: 1760×1130×1245mm
 40GP: 26 pallets/container, 936pcs/container

EINNOVA SOLARLINE ENERGY CORP. LIMITED

210000 Nanjing
 PEOPLE'S REPUBLIC OF CHINA
 TEL: +86-25-8479-2033
 Cell: +86-138-13088384
 EMAIL: emma.wu@einnova-solarline.com
 Website: www.einnova-solarline.com

Specification

Cell type	N type mono crystalline 182mm
Half-cell quantity	108 (6×18)
Dimension	1722×1134×30
Weight	21kg±3%
Glass	3.2mm, tempered and AR coated
Frame	Black Anodized Aluminum Alloy
Junction Box	IP68
Cable	1000mm (can be customized)

The company reserves the right of final right of adjustment of this file.