



Solar Roof Tiles

Pmax: 12W/ 8W

TOPCON Solar Cell

25.1%

Efficiency Up To

FEATURES

Superior Waterproof Performance

Highly resistant to water infiltration
Durable in extreme weather
Ensures long-term roof protection

Lightweight Design


Only 1.3KG
Reduces structural load
Easy to transport and handle

Easy Installation & Construction

Quick installation
Compatible with standard roofing methods
Saves time and labor costs

Standard Tile Dimensions

Matches traditional tile sizes
Seamless integration
No need for additional structural modifications



10_{year}

Quality warranty

25_{year}

Performance
warranty

- 1st year degradation less than 1%,
- 25 years power output 89.4% guaranteed.


★ ISO 9001: 2015 Quality Management
★ ISO14001: 2015 Environment

Strictly complying with IEC 61215 and
IEC 61730 standards

SPECIFICATION

Model	ESM-R12W full black	ESM-R8W terra cotta
Pmax	12W	8W
Voc	3.42V	3.42V
Isc	4.51A	3.10A
Vmpp	2.9V	2.9V
Imp	4.26A	2.76A
Weight	1.3kg	1.3kg
Product size	400*300*39mm	
Cell Size	210*52.5mm	
Solar Cell QTY	5pcs	
Cable Length	350mm(can be customized)	
QTY/Pallet	18pcs/box; 24boxes/pallet;432pcs/pallet	
Dimension	930*1300*1900mm	
QYT in 20HQ	5184pcs	
QTY in 40HQ	10368pcs	

PRODUCT DRAWING



APPLICATION



EINNOVA SOLARLINE ENERGY CORP. LIMITED 210000 Nanjing PEOPLE'S REPUBLIC OF CHINA

TEL: +86-25-8479-2033 Cell: +86-138-13088384

EMAIL : emma.wu@einnova-solarline.com

Website: www.einnova-solarline.com

